

CJPJ/SC-3.6/6kV、CJPF/SC-3.6/6kV 电缆结构参数 表 1

规格 mm ²	导体单丝直径 mm	导体直径 mm	绝缘标称厚度 mm	护套标称厚度 mm	电缆近似外径 mm	电缆近似重量 kg/km
1×10	1.35	4.0	2.5	1.3	15.6	364.7
1×16	1.70	5.0	2.5	1.3	16.7	453.1
1×25	2.19	6.0	2.5	1.3	17.8	571.1
1×35	2.60	7.0	2.5	1.4	18.9	700.4
1×50	3.00	8.2	2.5	1.4	20.2	885.2
1×70	2.18	10.0	2.5	1.5	22.2	1144.1
1×95	2.58	11.6	2.5	1.6	23.9	1446.2
1×120	2.91	13.0	2.5	1.6	25.4	1743.2
1×150	2.31	14.4	2.5	1.7	26.9	2089.2
1×185	2.58	16.1	2.5	1.7	29.2	2524.7
1×240	2.96	18.4	2.6	1.8	31.9	3176.3
1×300	2.58	20.6	2.8	1.9	34.7	3891.5
1×400	2.91	23.4	3.0	2.1	38.6	5093.1
1×500	3.30	26.6	3.2	2.2	43.3	6358.8
1×630	3.76	30.0	3.2	2.3	46.9	7842.3
3×10	1.35	4.0	2.5	1.8	30.9	893.0
3×16	1.70	5.0	2.5	1.9	29.6	956.1
3×25	2.19	6.0	2.5	2.0	31.9	1281.5
3×35	2.60	7.0	2.5	2.1	34.3	1640.2
3×50	3.00	8.2	2.5	2.2	37.6	2192.3
3×70	2.18	10.0	2.5	2.3	41.7	2915.2
3×95	2.58	11.6	2.5	2.4	45.5	3773.8
3×120	2.91	13.0	2.5	2.6	48.8	4621.9
3×150	2.31	14.4	2.5	2.7	52.0	5616.0
3×185	2.58	16.1	2.5	2.8	56.4	6809.8
3×240	2.96	18.4	2.6	3.0	62.3	8678.1
3×300	2.58	20.6	2.8	3.2	68.4	10733.1
3×400	2.91	23.4	3.0	3.5	75.9	14025.8
3×500	3.30	26.6	3.2	3.8	85.2	17500.5
3×630	3.76	30.0	3.2	4.1	93.1	21775.4